

Assessment of Performance Report ***n.1880-AoP-068-23 - rev.01***

For the purposes of Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this Assessment of Performance Report under AVCP system 3 applies to the construction products

KUBE 4, KUBE 3, KUBE 5, OCTO+, BABINA+, MERETHE+, KRISTIN+, ROMA

residential solid fuel burning appliances (roomheaters) fired by wood pellet, without hot water supply
placed on the market under the name or trademark of

**NORSK KLEBER AS
SKANSEN 29
2670 OTTA
NORWAY**

This Assessment of Performance Report attests that the performance of the above-mentioned construction product has been assessed in accordance with the harmonized standard

EN 16510-2-1:2022

under AVCP system 3 with regard to the essential characteristics listed in Annex 1.

Basis of the assessment: testing and issuing of Test report 1880-CPR-068-23 - rev.01.

This Assessment of Performance Report has been drawn up in accordance with the GNB Position Paper NB-CPR 23/836 and covers only the essential characteristics listed in Annex 1. It is not an exhaustive statement of the performance of the product. The manufacturer is responsible for the Declaration of Performance of the product and can declare the performance of other essential characteristics than those mentioned above.

This Assessment of Performance report is not considered a product certificate or a document to directly accompany neither the product nor the Declaration of Performance. See CPR Article 4(3).

This Assessment of Performance Report will remain applicable, under the manufacturer's responsibility, as long as neither the harmonised standard, the construction product, nor the AVCP methods are modified significantly.

January 16, 2026

Head of laboratory
dr.ssa Claudia Marcuzzi

ANNEX 1

Essential characteristic	Performance	Basis for the assessment of performance
Mechanical resistance and stability		
Load bearing capacity	80 kg	declared by the manufacturer
Safety in case of fire		
Protection of combustible materials Minimum distance to combustible materials	bottom d _B 0 mm side d _S 200 mm rear d _R 350 mm top d _C 750 mm floor d _F 0 mm side d _L 0 mm front d _P 700 mm	Test report n. 1880-CPR-068-23 - rev.01
Hygiene, health and the environment		
Emission of combustion products [ref. at 13% O ₂]:	at nominal heat output: CO 250 mg/m ³ NOx 92 mg/m ³ OGC 5 mg/m ³ PM 9 mg/m ³	Test report n. 1880-CPR-068-23 - rev.01
Safety and accessibility in use		
Data for installation to a chimney at nominal heat output:		
Flue gas outlet temperature	164°C	Test report n. 1880-CPR-068-23 - rev.01
Minimum flue draught	12 Pa	
Flue gas mass flow	8,2 g/s	
Data for installation to a chimney regarding fire safety on safety test heat output:		
Fire safety of installation to a chimney	T200 G	declared by the manufacturer
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal heat output:		
Space heat output	10,9 kW	Test report n. 1880-CPR-068-23 - rev.01
Efficiency	91,5 %	
Space heating efficiency		
Seasonal space heating efficiency at appliance's nominal heat output	81,5 %	Test report n. 1880-CPR-068-23 - rev.01
Energy efficiency	EEI 123	
	class A+	
Electric power consumption at appliance's nominal heat output, if existing	-- kW	
Electric power consumption at appliance's part load heat output, if existing	-- kW	
Standby mode power consumption, if existing	-- kW	
Sustainable use of natural resources		
Environmental sustainability	NPD	declared by the manufacturer